

## Piede Snodato in Acciaio Zincato

### Zinc Plated Articulated Foot

COD.	A	M	B	H	Carico Max Statico Maximum Load daN	U.V.
A4EM40/8	40	08MA	56	25	400	4
A4EM40/10	40	10MA	70	25	400	4
A4EM40/12	40	12MA	70	25	400	4
A4EM60/12	60	12MA	70	23	600	4
A4EM60/16	60	16MA	70	23	600	4
A4EM80/16	80	16MA	128	23	1000	4
A4EM80/20	80	20MA	128	25	1000	4
A4EM100/16	100	16MA	165	25	1200	4
A4EM100/20	100	20MA	165	25	1200	4

#### Caratteristiche

##### Caratteristiche Specifiche:

Livellamento laterale di 15° circa

**Materiale Base:** Acciaio cromato

**Corredo Base:** Suola antiscivolo in dotazione

**Materiale Stelo:** Acciaio zincato

**Tipo Stelo:** Snodato (testa sferica)

##### Presentazione Prodotto:

Stelo fornito già assemblato alla base

#### Product specification

##### Specific Features:

Lateral adjustment approx 15°

**Base Material:** Chromium plated Steel

**Base Outfit:** Non-slip pad enclosed

**Spindle Material:** Zinc plated steel

**Spindle Type:** Swivel (spheric head)

##### Product Presentation:

Spindle supplied already assembled to the base

